


STREET 90° ELBOW SILVER BRAZE

Intended for use with Class 200 or 700
Copper Nickel Tube IAW MIL-T-16420
Copper Tube IAW MIL-T-24107
Brass Tube IAW MIL-T-20168

Specification: MIL-F-1183
Pressure Rating: 400 PSIG (WOG)

SERVICE RATING TABLE				
Nominal Pipe Size (INCHES)	Maximum Working Pressure (LB/IN ²)	Maximum Temperature (°F)	Maximum Working Pressure (LB/IN ²)	Maximum Temperature (°F)
1/4 through 6	200	425	400	150
Above 6	150	425	250	150



BRONZE
ASTM B61 / QQ-C-390 / MIL-B-16541
(ALLOY C90300 / C92200)

AVAILABLE ALLOY: BRONZE

NOMINAL PIPE SIZE	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
SMI P/N	ST9BSB040	ST9BSB060	ST9BSB100	ST9BSB150	ST9BSB200	ST9BSB250	ST9BSB300	ST9BSB400
A	1.19	1.25	1.47	1.19	1.44	2.25	2.47	2.88
B	0.700	0.855	1.020	1.250	1.535	1.900	2.160	2.675
C	0.540 MIN - 0.543 MAX	0.675 MIN - 0.678 MAX	0.840 MIN - 0.843 MAX	1.050 MIN - 1.053 MAX	1.315 MIN - 1.318 MAX	1.660 MIN - 1.663 MAX	1.900 MIN - 1.905 MAX	2.375 MIN - 2.380 MAX
D	17/64	5/16	3/8	13/32	7/16	1/2	5/8	21/32
E	.537 MIN - .540 MAX	.672 MIN - .675 MAX	.837 MIN - .840 MAX	1.047 MIN - 1.050 MAX	1.312 MIN - 1.315 MAX	1.657 MIN - 1.660 MAX	1.897 MIN - 1.900 MAX	2.372 MIN - 2.375 MAX

NOTES: Brazing rings IAW QQ-B-654, BCuP-5 are to be used with grooved fitting ends.
Fittings may be ordered with reduced ends.