


TEE

SOCKET WELD

Specification: NAVSEA DWG 803-6397430
Pressure Rating: 400 PSIG (WOG)

Intended for use with Class 200 or 700
Copper Nickel Tube IAW MIL-T-16420

SERVICE RATING TABLE				
Nominal Pipe Size (INCHES)	Maximum Working Pressure (LB/IN ²)	Maximum Temperature (°F)	Maximum Working Pressure (LB/IN ²)	Maximum Temperature (°F)
1/4 through 6	200	425	400	150
Above 6	150	425	250	150



AVAILABLE ALLOYS: CUNI 90/10 & CUNI 70/30

NOMINAL PIPE SIZE	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"
SMI P/N (90/10)	T9SW040	T9SW060	T9SW100	T9SW150	T9SW200	T9SW250	T9SW300	T9SW400	T9SW450	T9SW500	T9SW550	T9SW600
SMI P/N (70/30)	T7SW040	T7SW060	T7SW100	T7SW150	T7SW200	T7SW250	T7SW300	T7SW400	T7SW450	T7SW500	T7SW550	T7SW600
A	0.710	0.820	1.010	1.180	1.430	1.690	1.840	2.120	2.700	3.080	3.420	3.790
B	0.945	1.096	1.275	1.503	1.780	2.129	2.387	2.908	3.408	4.041	4.541	5.097
C	.545 (+/- .030)	.680 (+/- .030)	.845 (+/- .030)	1.055 (+/- .030)	1.320 (+/- .030)	1.665 (+/- .030)	1.905 (+/- .030)	2.380 (+/- .046)	2.880 (+/- .051)	3.505 (+/- .055)	4.005 (+/- .055)	4.505 (+/- .060)
D	25/94	5/16	3/8	13/32	7/16	1/2	5/8	23/35	25/32	77/93	7/8	29/32

NOTES: Fittings may be ordered with reduced ends and/or female threads.